

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Sheet 1 of 11




Figure 1

Sheet 2 of 11

Frame	Sign and Training Pattern					
	Slot 1	Slot 2	Slot 3	Slot 4	Slot 5	Slot 6
1	+R	-T	-R	+T	-R	-T
2	+T	+R	-T	+R	+T	-R
3	+R	+T	-R	+T	-T	-R
4	-T	+T	+R	+T	-T	+T
5	+T	-R	-T	+T	-T	+R
6	-T	+T	+T	-T	-R	-T
7	+T	-T	+T	+R	+T	-T
8	-R	-T	+T	-T	+T	-T
9	+T	+R	+T	-T	+R	-T
10	+R	-T	+T	+R	-T	-R
11	-T	+T	-T	-T	+T	+T
12	+T	-R	-T	+T	+R	+T
13	-R	-T	+T	-R	-T	+T
14	-T	+T	-R	+T	-T	+R
15	-T	+T	+R	-T	+R	+T
16	-T	-R	+T	-R	-T	+R
17	-T	-T	+R	+T	+T	-T
18	+T	+R	-T	-T	+T	-T
19	-R	+T	-T	-T	-R	+T
20	+T	-T	-T	-R	+T	+T

The "T" in the table represents a training amplitude.
The "R" in the table represents a reference amplitude.
The "+" or "-" represents the sign of the symbol.

Figure 2

Sheet 3 of 11




Figure 3

Sheet 4 of 11




Figure 4

Sheet 5 of 11




Figure 5

Sheet 6 of 11




Figure 6

Sheet 7 of 11




Figure 7




Figure 8

PCM - an 8-bit μ law or A-law digital symbol transmitted over the network. The symbol represents a signal amplitude.
Llinear - the linear value corresponding to the digital symbol (see G.711).
Analog - the local twisted-pair from the central office to the modem.




Figure 9

$$\text{Error} = \frac{\sum_{n=\text{Unicode } 72}^{\text{Unicode } 105} |\text{Received Sample}_n \cdot \text{Test Fraction} - \text{SLICED}[\text{Received Sample}_n \cdot \text{Test Fraction}]|}{\text{Test Fraction}}$$

SLICED[x] - results in the G.711 value closest to x.

Unicode# - refers to PCM symbols sent by the server (see V.90 specification)

Received Sample_n - an average received value from the DIL sequence corresponding to Ucode#.

Test Fraction - a value between 1.0 and 0.25 that is adjusted to result in a minimum error

Figure 10

Sheet 9 of 11

U - Code Sent	Avg. Received Value	Using 0.5 as the Text Fraction	Absolute Error	Using 0.5077 as the Text Fraction	Absolute Error
90	6673	3337	51	3388	0
91	6925	3463	53	3516	0
92	7178	3589	55	3644	0
93	7430	3715	57	3772	0
94	7682	3841	59	3900	0
95	8060	4030	62	4092	0
96	8060	4030	62	4092	0
97	8564	4282	66	4348	0
98	9068	4534	70	4604	0
99	9573	4787	73	4860	0
100	10077	5039	77	5116	0
101	10581	5291	81	5372	0
102	11085	5543	85	5628	0
103	11590	5795	89	5884	0
104	12094	6047	93	6140	0
105	12598	6299	97	6396	0

Figure 11

Sheet 10 of 11




Figure 12

Sheet 11 of 11




Figure 13